



ULTIMATE-DESIGN
recycled rubber flooring
is an ideal choice for
the varying demands of
the commercial market.

- *Environmentally Friendly*
- *Durable*
- *Shock & Sound Absorbing*
- *Anti-Fatigue*
- *Easy to Clean*
- *Made in USA*
- *FloorScore Certified*
- *Custom Sizing & Colors*
- *Easy Installation*
- *Comes in Roll & Tile Options*

ULTIMATE-DESIGN ROLLED RUBBER AND TILES BENEFITS

RETAIL SPACES, OFFICES & RESTAURANTS	SPORTS FACILITIES AND ARENAS
POOLSIDE WALKWAYS	HEALTH & FITNESS CENTERS
HOSPITALS, SCHOOLS & LIBRARIES	GOLF & SKI RESORTS
AEROBIC FITNESS & YOGA STUDIOS	HOSPITALITY AREAS

Admired by architects and designers. Recommended and selected by specifiers. Preferred by green building managers. ULTIMATE-DESIGN recycled rubber flooring has proven to be the floor of choice by those who desire sustainable, environmentally friendly, resilient flooring. ULTIMATE-DESIGN is available in a large number of colors and design options. Manufactured from vivid EPDM color granules - which consist of 28% post-industrial recycle - ULTIMATE-DESIGN rubber flooring can be blended to match your custom color palette, achieving virtually any color range for an unlimited number of applications. Schools, hospitals, retail spaces and corporate office buildings are common installations. Ultimate Design is FloorScore certified and meets the CHPS criteria for strict indoor air quality standards. In addition, ULTIMATE-DESIGN can contribute to multiple LEED credits under the U.S. Green Building Council's rating system.



ULTIMATE-DESIGN SPECIFICATIONS



TYPICAL PROPERTIES - ROLLS

*WIDTH

Standard: 3' & 4' (0.91M & 1.22M)

*THICKNESS

Standard:

3.4MM (.134"), 4MM (.157"), 6MM (.236"), 8MM (.300"), 9.5MM (.375")

*LENGTH

Standard: 25' (7.62M) & 50' (15.24M)

COLORED EPDM GRANULATE

0.0394" (1MM) TO 0.1181" (3MM)

BINDER

URETHANE

*CUSTOM AVAILABLE

* 3' (.91M) AVAILABLE AS CUSTOM WIDTH

NOTE:

Physical properties can vary by product color.



TYPICAL PROPERTIES - TILES

TILE SIZES

Interlocking

18" X 18" (0.4572M²)

24" X 24" (0.61M²)

36" X 36" (0.91M²)

48" X 48" (1.2192M²)

Square

24" X 24" (0.61M X 0.61M)

36" X 36" (0.91M X 0.91M)

36" X 36" (0.91M²)

48" X 48" (1.2192M²)

*THICKNESS

Standard: 3.4MM (.134"), 4MM (.157"), 6MM (.236"), 8MM (.300"), 9.5MM (.375")

TOLERANCE

+/- 0.020"

COLORED EPDM GRANULATE

0.0394" (1MM) TO 0.1181" (3MM)

BINDER

URETHANE

*CUSTOM AVAILABLE



ULTIMATE-DESIGN SPECIFICATIONS

TEST TYPE	ASTM	RESULT
SHORE HARDNESS	D-2240	60 +/- 5
DENSITY	D-395	70-85 LBS./CU.FT.
ELONGATION (AT BREAK)	D-412	> 90% @ 50% COLOR
TENSILE STRENGTH	D-412	> 300 PSI @ 50% COLOR
COMPRESSION SET	D-395	-14.1% @ 25%
VOC EMISSIONS	D-5116	0.5 MG/M ² OR LESS
RESISTANCE TO CHEMICALS	F-925-02	NO CHANGE
STATIC LOAD LIMIT	F-970	400 LB/IN
CRITICAL RADIANT FLUX*	E-648	CLASS II
COEFFICIENT OF FRICTION	C-1028	> 0.75

*TESTED AT 80% COLOR

MAINTENANCE & FLOOR CARE

Maintenance and floor care depend on the desired appearance of the installed product and the type of equipment used to maintain the flooring. Use only Ultimate RB recommended cleaners, disinfectant, and neutral PH, non-petroleum products. Do not use harsh chemicals. For specific products recommended by Ultimate RB, visit www.UltimateRB.com.

WARRANTY

Ultimate RB Rolled Rubber products carry a 5-year limited warranty for defects in material and workmanship. Refer to UltimateRB.com for limited warranty document.

COLOR OPTIONS

Please visit www.UltimateRB.com for current available color options.