



For over 25 years, Ultimate RB has been the premier supplier to the farm, equestrian, and pet communities. Equestrians who demand the very best have chosen Ultimate RB Stall Mats for maximum protection, support, and traction. All stall mats are covered by our 15-year limited warranty, and made in the USA.

ULTIMATE RB STALL MATS BENEFITS

RECYCLED RUBBER	FULL THICKNESS	ISO 9001
DURABLE	VERSATILE	15-YEAR WARRANTY
SUPERIOR COMFORT	TRACTION/SAFETY	ENVIRONMENTALLY FRIENDLY
MADE IN USA	CUSTOM SIZING	HIGH QUALITY

For over 25 years, Ultimate RB has been the premier supplier to the equestrian community of recycled rubber horse stall matting and rolled rubber for use in horse trailers. Ultimate RB builds quality matting products that are known and trusted to provide excellent traction, durability, and comfort. With a broad range of standard sizes, expandable kit, and unlimited custom sizing capability, we can provide a product to meet any need.

STALL MATS

Custom-formulated, high strength polyurethane binders, similar to those used in synthetic running tracks, are used in the construction of stall mats. When they are combined with recycled tire crumb in our unique manufacturing process, an extremely durable material is produced. When you ask for Ultimate RB Stall Mats, you can be sure that the mats you take home will be high quality, environmentally friendly, and made in the USA. We stand fully behind each mat we produce with a 15 year limited warranty.

STANDARD SIZES

4'x6', 4'x7' and 4'x8' with thicknesses of 1/2" or 3/4".



FLOORING SPECIFICATIONS



TYPICAL PROPERTIES

MAT SIZES

Standard:

4' x 6' (1.2M x 1.8M)

4' x 7' (1.2M x 2.1M)

4' x 8' (1.2 x 2.4M)

THICKNESS

Standard:

0.5" (12.7MM)

0.75" (19MM)

BLACK SBR GRANULATE

0.5" (12.7MM)

BINDER

URETHANE

SURFACE

FLAT ONE SIDE, WIRE MESH TEXTURE/ANTI-SKID SURFACE BACK



STALL MATS SPECIFICATIONS

TEST TYPE	ASTM	RESULT
DENSITY	D-395	50-60 LBS./CU.FT.
COMPRESSION SET	D-395	-21.7% @ 25%
COEFFICIENT OF FRICTION	C-1028	< 0.8
SHORE HARDNESS	D-2240	65 +/-5
ELONGATION	D-412	140%
TENSILE STRENGTH	D-412	> 270 PSI
CHEMICAL RESISTANCE	F-925	NO CHANGE

NOTE:

Physical properties can vary by product type.
Information above applies to this product only.

MAINTENANCE & FLOOR CARE

Use only Ultimate RB recommended cleaners, disinfectant, and neutral PH, non-petroleum products. Do not use harsh chemicals. For specific products recommended by Ultimate RB, visit www.UltimateRB.com or call the number listed below.

WARRANTY

Ultimate RB Stall Mats carry a 15-year limited warranty, one of the longest warranties in the industry. Refer to UltimateRB.com for limited warranty document.

