



Ultimate RB has been manufacturing EPDM rubber for use in running tracks, playgrounds, flooring, and a myriad of other applications since 1989. With all aspects of formulation and manufacturing conducted in-house, we can offer product quality and consistency that no competitor can match.

EPDM GRANULES BENEFITS

WEATHER & SLIP RESISTANT	AMERICAN MADE	CUSTOM OPTIONS
DESIGN FLEXIBILITY	WARRANTY	RANGE OF SIZES
COLOR OPTIONS	IPEMA CERTIFIED	QUALITY MATERIALS
MAINTENANCE EASE	DURABLE	ECO-FRIENDLY

Ultimate RB has been manufacturing EPDM Granules for use in running tracks, playgrounds, flooring, and a myriad of other applications since 1989. Our process begins with formulation development and the procurement of quality raw materials. Then we proceed with mixing, curing, and granulating. This is a highly demanding and technical process that requires strict adherence to quality control standards at each step.

In addition to quality assurance, Ultimate RB provides value in several other ways. From a technical standpoint, we can modify our formulations to meet the varying physical properties that our customers require. From an aesthetic standpoint, we offer over 100 different colors. We can also develop custom colors to meet any need, and provide a wide range of granule sizes from small to large. Finally, from a logistics and cost standpoint, we offer many of the more popular colors at several strategic warehouse locations across the country.

With this combination of quality control, technical assistance, product variety, and logistical savings, Ultimate RB can provide an optimal EPDM Granules for your application.



Rev 5/19 | Ult. #15

EPDM GRANULES SPECIFICATIONS

TYPICAL PROPERTIES

GRANULE

BLACK SBR
BLACK EPDM
VIRGIN BLACK EPDM
COLORED EPDM

SIZES (available in all colors)

.5-1MM
1-3MM
1-4MM
2-4MM
1-5MM
3-6MM

PACKAGING (2,200 LB. per skid)

55 LB. POLY BAGS
2,000 LB. BULK TOTE BAGS
1,000 LB. BULK TOTE BAGS
1,100 LB. BULK TOTE BAG

EPDM SPECIFICATIONS

TEST TYPE	ASTM	RESULT
SHORE HARDNESS	D-2240	60 +/- 5
BULK DENSITY	---	41 LBS./CU.FT.
SPECIFIC GRAVITY	D-297	1.55 + OR -.03
MOISTURE	D-1509	1% MAX
FREE FLOWING AGENT ADDITIVE	---	2% PER WEIGHT MAX

PROPERTIES	ASTM	MIN	MAX
ACETONE EXTRACT	D-297	10	20
ASH CONTACT		35	65
RUBBER HYDROCARBON	---	23	30

WARRANTY

Ultimate RB rubber products carry a limited warranty for defects in material and workmanship. Refer to UltimateRB.com to limited warranty document.

COLOR OPTIONS

