



MEGA-LOCK tiles are an ideal choice for very demanding applications where flooring protection, sound dampening, superior traction, and anti-fatigue qualities are required.

- Recycled Rubber
- Made in USA
- Slip Resistant
- Non-toxic
- FloorScore Certified
- Environmentally Friendly
- Easy Installation
- Sound & Shock Absorbing
- Easy Maintenance

MEGA-LOCK TILE BENEFITS

COMMERCIAL/HOME GYMS	SPIKE PROTECTION	WAREHOUSES
MILITARY BASES	BOAT DOCKS	WORK AREAS
ICE RINKS	LOCKER ROOMS	CARDIO DECKS
SKI LODGES	GARAGES	PATIOS & DECKS

Protect concrete and wood sub-floors as well as free weight equipment with Ultimate RB MEGA-LOCK interlocking rubber gym tiles. Each tile is made from dense .5"-.75" thick rubber derived from used car and truck tires and are designed to absorb shock and impact from heavy kettlebells, barbells, and dumbbells. Tiles fit together just like a big puzzle, making for an easy installation that needs no adhesive. Custom trimming of your tiles can be done with a razor knife, straight edge, and measuring tape.

BLACK MEGA-LOCK TILES

Commonly used for weightlifting applications placed beside weight benches to absorb the shock of dumbbells and barbells. This protective material has the added benefit of including interlocking tabs which locks the tiles together so they cannot move. Choose between center, edge, and corner tiles to make installation easier and cleaner looking.

MEGA-LOCK TILES WITH 10% COLOR FLECK

Add flooring protection and beautiful color to your gym with our Ultimate RB MEGA-LOCK tiles with 10% color EPDM content. Color flecks not only brighten up your gym, but help camouflage dirt, debris, and tile seams. Ultimate RB MEGA-LOCK tile choices include centers, edges and corners.



ULTIMATE RB MEGA-LOCK SPECIFICATIONS

TYPICAL PROPERTIES

TILE SIZES

Standard:
30" X 30"

COVERAGE

6.25 SQ FT/TILE

THICKNESS

Standard: 0.5" AND 0.75"

BINDER

POLYURETHANE

COLORED EPDM GRANULATE

1MM TO 3MM

NOTE:

Physical properties can vary by product type. Information above applies to this product only.

Ultimate RB MEGA-LOCK contains up to 96% recycled rubber material, manufactured in the USA, and they are all covered by our Limited Warranties.

MEGA-LOCK SPECIFICATIONS


TEST TYPE

ASTM

RESULT

DENSITY	D-395	50-60 LBS./CU.FT.
COMPRESSION SET	D-395	-21.7% @ 25%
COEFFICIENT OF FRICTION	C-1028	< 0.8
SHORE HARDNESS	D-2240	65 +/-5
ELONGATION	D-412	140%
TENSILE STRENGTH	D-412	> 270 PSI
CHEMICAL RESISTANCE	F-925	NO CHANGE

COLOR OPTIONS



MAINTENANCE & FLOOR CARE

Maintenance and floor care depend on the desired appearance of the installed product and the type of equipment used to maintain the flooring. Use only Ultimate RB recommended cleaners, disinfectant, and neutral PH, non-petroleum products. Do not use harsh chemicals. For specific products recommended by Ultimate RB, visit UltimateRB.com

WARRANTY

Ultimate RB MEGA-LOCK tiles carry a 15-year limited warranty for defects in material and workmanship. Refer to UltimateRB.com for limited warranty document.