



Ultimate RB Rolled Rubber flooring provides a durable, resilient surface for dog play, agility practice, and competition, while also allowing for easy cleaning and maintenance.

ULTIMATE RB ROLLED RUBBER BENEFITS

ENVIRONMENTALLY FRIENDLY	AESTHETIC	RECYCLED RUBBER
DURABLE	ANTI-FATIGUE RESILIENCE	CUSTOM SIZING & COLORS
SHOCK & SOUND ABSORBING	EASY TO CLEAN	EASY INSTALLATION
VERSATILE	AMERICAN MADE	

Ultimate RB Rolled Rubber flooring provides a durable, resilient surface for dog play, agility practice, and competition, while also allowing for easy cleaning and maintenance. The anti-fatigue qualities of the soft rolled rubber material reduce stress on the joints and muscles of pets and their human caretakers, and the superior traction of rubber flooring is unequalled. From doggy daycare facilities to canine agility courses, rolled rubber is an ideal flooring material selection.

STANDARD PRODUCTS

Ultimate RB manufactured standard rolled rubber products in thicknesses including 8 mm and 9.5 mm. These standard rolls are 4' x 25' and 4' x 50'. In addition to black, our inventory of standard products includes rolls 20% fleck color in Grey, Blue, Red, Green, Blue/Gray, and Cocoa/Eggshell.

COLORS

Ultimate RB produces highly colored flooring material that can be cut to your specifications.



FLOORING SPECIFICATIONS



TYPICAL PROPERTIES

***WIDTH**
Standard: 4' (1.2M)

***THICKNESS**
Standard: 0.25" (6.4MM) & 0.375" (9.5MM)

***LENGTH**
Standard: 25' (7.6M) & 50' (15.2M)

COLORED EPDM GRANULATE
0.0394" (1MM) TO .1181" (3MM)

BINDER
URETHANE

* CUSTOM AVAILABLE
* 3' (.91M) AVAILABLE AS CUSTOM WIDTH

NOTE:





Physical properties can vary by product type.
Information above applies to this product only.



ROLLED RUBBER SPECIFICATIONS

TEST TYPE	ASTM	RESULT
SHORE HARDNESS	D-2240	65 +/- 5
DENSITY	D-792	80 LBS./CU.FT.
ELONGATION (AT BREAK)	D-412	300%
TENSILE STRENGTH	D-412	
TABER ABRASION	D-3884	200 PSI
FLAME SPREAD	E-84	2.34
SMOKE DENSITY	E-84	65
COMPRESSION SET	D-395	< 450
VOC EMISSION	D-5116	9.7%
RESISTANCE TO CHEMICALS	F-925-02	0.5 MG/M ² OR LESS
STATIC LOAD LIMIT	F-970	NO CHANGE
ELECTROSTATIC PROPENSITY	AATCC 134-1996	-0.001 IN
CRITICAL RADIANT FLUX	E-648 0.52	NEG 0.6 KV W/CM2

COLOR OPTIONS



MAINTENANCE & FLOOR CARE

Use only Ultimate RB recommended cleaners, disinfectant, and neutral PH, non-petroleum products. Do not use harsh chemicals. For specific products recommended by Ultimate RB, visit www.UltimateRB.com, or call the number listed below.

WARRANTY

Ultimate RB Rolled Rubber products carry a 5-year limited warranty for defects in material and workmanship.