



For over 25 years, Ultimate RB has been the premier supplier to the farm, equestrian, and pet communities. Ultimate RB Trailer Rolls and Mats are used on trailer floors, walls, and ramps to help ease the stress on animals in transit by providing maximum protection, support, and traction.

ULTIMATE RB TRAILER ROLLS & MAT BENEFITS

RECYCLED RUBBER	EASILY CLEANED	CUSTOM SIZING
DURABLE	FULL THICKNESS	QUALITY/WARRANTY
SUPERIOR COMFORT	EASY INSTALLATION	ENVIRONMENTALLY FRIENDLY
PREVENTS DAMAGE	TRACTION/SAFETY	

Since its inception in 1985, Ultimate RB has been the premier supplier and manufacturer of recycled rubber horse stall matting and rolled rubber for use in horse trailers. Ultimate RB builds quality matting products that are known and trusted to provide excellent traction, durability, and comfort. When you ask for equine rolls and mats you can be sure that the product you take home will be high quality, environmentally friendly, and made in the USA. We stand fully behind each mat we produce with a 15-year limited warranty.

HORSE TRAILER MATS

Ultimate RB trailer mats are used on trailer floors, walls, and ramps to help ease the stress on animals in transit by providing maximum protection, support, and traction.

HORSE TRAILER ROLLS

The rolled rubber material can be affixed to any surface with commonly available urethane adhesives and can easily be cut to any dimension or shape with a standard utility knife.



FLOORING SPECIFICATIONS



TYPICAL PROPERTIES

MAT SIZES

Standard:

4' X 6' (1.2M X 1.8M)
4' X 7' (1.2M X 2.1M)
4' X 8' (1.2 X 2.4M)

THICKNESS

Standard:

0.5" (12.7MM)
0.75" (19MM)

BLACK SBR GRANULATE

0.5" (12.7MM)

BINDER

URETHANE

SURFACE

FLAT ONE SIDE, WIRE MESH TEXTURE/ANTI-SKID SURFACE BACK

Ultimate RB trailer mats can also be custom cut to fit the nose section of a trailer or any other location per your request.



ULTIMATE-TOUGH SPECIFICATIONS

TEST TYPE	ASTM	RESULT
SHORE HARDNESS	D-2240	65 +/- 5
DENSITY	D-792	60-80 LBS./CU.FT.
ELONGATION (AT BREAK)	D-412	95% - 120%*
TENSILE STRENGTH	D-412	260 - 340 PSI*
COMPRESSION SET	D-395	-4.8%
VOC EMISSIONS	D-5116	0.5 MG/M ² OR LESS
RESISTANCE TO CHEMICALS	F-925-02	NO CHANGE
STATIC LOAD LIMIT	F-970	PASSES, 150 PSI
DIE- C TEAR	D-624	80 MIN
SURFACE FLAMMABILITY	D-2859	PASS
COEFFICIENT OF FRICTION	D-1894-95	>0.8*

*VARIES BASED ON COLOR

NOTE:

Physical properties can vary by product type. Information above applies to this product only.



TYPICAL PROPERTIES

ROLL SIZES

Standard:

4' X 25' (1.2M X 7.6M)
4' X 50' (1.2M X 15.2M)

THICKNESS

Standard:

0.25" (6.4MM)
0.375" (9.5MM)
CUSTOM UP TO 12MM

WIDTH

Standard: 4' (1.2M)

BINDER

URETHANE



ROLL DIMENSIONS

*WIDTH

Standard:

4 FT. (1.22M)

*LENGTH

Standard:

25 FT. & 50 FT.

WIDTH TOLERANCES

48" CUT @ 48.5" +/- 0.24"

COLORED EPDM GRANULATE

1MM TO 3MM

*THICKNESS

Standard:

4 M M TO 12MM
+/- 0.015"

BINDER

URETHANE

The color concentration of the standard rolls and tiles is 20%.

*CUSTOM AVAILABLE

*3 FT. AVAILABLE AS CUSTOM WIDTH

MAINTENANCE & FLOOR CARE

Use only Ultimate RB recommended cleaners, disinfectant, and neutral PH, non-petroleum products. Do not use harsh chemicals. For specific products recommended by Ultimate RB, visit www.UltimateRB.com or call the number listed below.

WARRANTY

Ultimate RB Trailer Rolls and Mats carry a 5-year limited warranty. Refer to UltimateRB.com for limited warranty document.

Rev 7/19 | Ult. #8



1430 North Main St.
Delphos, OH 45833
T. 419.692.3005

904 NE 10th Ave.
McMinnville, OR 97128
T. 503.472.4691



© 2019 Ultimate RB
All rights reserved
www.UltimateRB.com