



ULTIMATE-DESIGN
recycled rubber flooring
is an ideal choice for
the varying demands of
the commercial market.

- *Environmentally Friendly*
- *Durable*
- *Shock & Sound Absorbing*
- *Anti-Fatigue*
- *Easy to Clean*
- *Made in USA*
- *FloorScore Certified*
- *Custom Sizing & Colors*
- *Easy Installation*
- *Comes in Roll & Tile Options*




ULTIMATE-DESIGN ROLLED RUBBER AND TILES BENEFITS

- | | |
|--------------------------------------|------------------------------|
| RETAIL SPACES, OFFICES & RESTAURANTS | SPORTS FACILITIES AND ARENAS |
| POOLSIDE WALKWAYS | HEALTH & FITNESS CENTERS |
| HOSPITALS, SCHOOLS & LIBRARIES | GOLF & SKI RESORTS |
| AEROBIC FITNESS & YOGA STUDIOS | HOSPITALITY AREAS |

Admired by architects and designers. Recommended and selected by specifiers. Preferred by green building managers. ULTIMATE-DESIGN recycled rubber flooring has proven to be the floor of choice by those who desire sustainable, environmentally friendly, resilient flooring. ULTIMATE-DESIGN is available in a large number of colors and design options. Manufactured from vivid EPDM color granules - which consist of 28% post-industrial recycle - ULTIMATE-DESIGN rubber flooring can be blended to match your custom color palette, achieving virtually any color range for an unlimited number of applications. Schools, hospitals, retail spaces and corporate office buildings are common installations. Ultimate Design is FloorScore certified and meets the CHPS criteria for strict indoor air quality standards. In addition, ULTIMATE-DESIGN can contribute to multiple LEED credits under the U.S. Green Building Council's rating system.



ULTIMATE-DESIGN SPECIFICATIONS

 ROLLS	 TILES	 ULTIMATE-DESIGN SPECIFICATIONS																																			
WIDTH Standard: 4' (1.22M)	Square 24" X 24" (0.61M X 0.61M)	<table border="1"> <thead> <tr> <th>TEST TYPE</th> <th>ASTM</th> <th>RESULT</th> </tr> </thead> <tbody> <tr> <td>SHORE HARDNESS</td> <td>D-2240</td> <td>60 +/- 5</td> </tr> <tr> <td>DENSITY</td> <td>D-395</td> <td>70-85 LBS./CU.FT.</td> </tr> <tr> <td>ELONGATION (AT BREAK)</td> <td>D-412</td> <td>> 90% @ 50% COLOR</td> </tr> <tr> <td>TENSILE STRENGTH</td> <td>D-412</td> <td>> 300 PSI @ 50% COLOR</td> </tr> <tr> <td>COMPRESSION SET</td> <td>D-395</td> <td>-14.1% @ 25%</td> </tr> <tr> <td>VOC EMISSIONS</td> <td>D-5116</td> <td>0.5 MG/M² OR LESS</td> </tr> <tr> <td>RESISTANCE TO CHEMICALS</td> <td>F-925-02</td> <td>NO CHANGE</td> </tr> <tr> <td>STATIC LOAD LIMIT</td> <td>F-970</td> <td>400 LB/IN</td> </tr> <tr> <td>CRITICAL RADIANT FLUX</td> <td>E-648</td> <td>CLASS II</td> </tr> <tr> <td>COEFFICIENT OF FRICTION</td> <td>C-1028</td> <td>> 0.75</td> </tr> </tbody> </table>	TEST TYPE	ASTM	RESULT	SHORE HARDNESS	D-2240	60 +/- 5	DENSITY	D-395	70-85 LBS./CU.FT.	ELONGATION (AT BREAK)	D-412	> 90% @ 50% COLOR	TENSILE STRENGTH	D-412	> 300 PSI @ 50% COLOR	COMPRESSION SET	D-395	-14.1% @ 25%	VOC EMISSIONS	D-5116	0.5 MG/M ² OR LESS	RESISTANCE TO CHEMICALS	F-925-02	NO CHANGE	STATIC LOAD LIMIT	F-970	400 LB/IN	CRITICAL RADIANT FLUX*	E-648	CLASS II	COEFFICIENT OF FRICTION	C-1028	> 0.75		
TEST TYPE	ASTM	RESULT																																			
SHORE HARDNESS	D-2240	60 +/- 5																																			
DENSITY	D-395	70-85 LBS./CU.FT.																																			
ELONGATION (AT BREAK)	D-412	> 90% @ 50% COLOR																																			
TENSILE STRENGTH	D-412	> 300 PSI @ 50% COLOR																																			
COMPRESSION SET	D-395	-14.1% @ 25%																																			
VOC EMISSIONS	D-5116	0.5 MG/M ² OR LESS																																			
RESISTANCE TO CHEMICALS	F-925-02	NO CHANGE																																			
STATIC LOAD LIMIT	F-970	400 LB/IN																																			
CRITICAL RADIANT FLUX*	E-648	CLASS II																																			
COEFFICIENT OF FRICTION	C-1028	> 0.75																																			
*THICKNESS Standard: 4MM (.157")	*THICKNESS Standard: 4MM (.157"),																																				
*LENGTH Standard: 25' (7.62M)	*CUSTOM AVAILABLE																																				
*CUSTOM AVAILABLE																																					
NOTE: Physical properties can vary by product color.																																					

MAINTENANCE & FLOOR CARE

Maintenance and floor care depend on the desired appearance of the installed product and the type of equipment used to maintain the flooring. Use only Ultimate RB recommended cleaners, disinfectant, and neutral PH, non-petroleum products. Do not use harsh chemicals. For specific products recommended by Ultimate RB, visit www.UltimateRB.com.

WARRANTY

Ultimate RB Rolled Rubber products carry a 5-year limited warranty for defects in material and workmanship. Refer to UltimateRB.com for limited warranty document.

COLOR OPTIONS

Please visit www.UltimateRB.com for current available color options.