



ULTIMATE-TOUGH™ Rolls & Tiles



Popular in health and fitness clubs, weight rooms, and ice rinks, **ULTIMATE-TOUGH** recycled rubber flooring is a champion in a wide variety of applications.

Features and Benefits

- High Impact Durability
- Manufactured in the USA
- Premium Recycled Rubber
- Slip and Impact Resistant
- Easy to Clean
- Environmentally Friendly
- Customizable
- Shock and Sound Absorbing
- FloorScore Certified

Applications:

- Weight Rooms & Gyms
- Multi-purpose Rooms
- Work Areas
- Jungle Gym & Play Areas
- School Cafeterias
- Concession Areas
- Ice Rink Walkways
- Factory Floors
- Ski & Snowboard Shops
- Home Gym Flooring
- Stationary Bike Matting
- Locker Rooms

ULTIMATE-TOUGH Products

Available in rolls or tiles, **ULTIMATE-TOUGH** is ideal for high-wear and high-impact spaces that require maximum subfloor protection. Home gyms, weight rooms, and basements all benefit from durable rubber tile. It is manufactured from post-consumer recycled rubber buffings with small percentages colored EPDM. **ULTIMATE-TOUGH** is the recommended choice for high-traffic active spaces. It provides excellent high-impact durability and superior slip resistance in wet or dry conditions. **ULTIMATE-TOUGH** also combines anti-fatigue and ergonomic comfort properties with very low maintenance. Containing up to 92% recycled content range and low VOC emissions, **ULTIMATE-TOUGH** is widely regarded as the premier "green" resilient flooring choice. It is available in rolls and interlocking and square tiles, and comes in 7 standard colors in variable thicknesses. Custom colors are also available.



ULTIMATERB.com

904 NE 10th Avenue
McMinnville, OR 97128
(800) 525-5530 ▪ (503) 472-4691

Main manufacturing/shipping locations include Oregon and Ohio.

Declare.





ULTIMATE-TOUGH™

Rolls & Tiles



Interlocking Tile Dimensions

Tile Sizes

	28.5" x 28.5" 5.64 sq ft
*Zip-Tile	Standard: 9.5mm thickness & 20% color
	24" x 24" 4 sq ft
*Tru-Lock Tile	Standard: 8mm thickness & 10% color

*Custom available



Roll Dimensions

*Width	Standard: 4 ft. (1.22m)
Width Tolerances	-0.00", +0.75"
*Thickness	Standard: 4mm to 12mm +/- 0.020"
*Length	Standard: 25 ft & 50 ft

The color concentration of the standard rolls and tiles is 20%.

*Custom available

* 3 ft. available as custom width


Color Options



NO. 106
Black



NO. 125
Grey



NO. 122
Blue/Grey




NO. 127
Blue



NO. 126
Green



NO. 294
Cocoa/Eggshell



NO. 229
Bright Red

Brick Red, Purple, Teal, Green/Grey and other custom colors available by request.



Specifications

Test Type	ASTM	Result
Shore Hardness	D-2240	65 +/- 5
Density	D-395	63-94 lbs/ft ³
Elongation (at break)	D-412	50-150%
Tensile Strength	D-412	200-400 PSI
Compression Set	D-395	-15 to -45% @ 25%
VOC Emissions	D-5116	0.5 mg/m ² or less
Resistance To Chemicals	F-925	No Change
Static Load Limit	F-970	Passes, 150 PSI
Surface Flammability	D-2895	Pass
Die-C Tear	D-624	80 min
Coefficient of Friction	D-1894	0.75-1.50
Durometer	D-2240	60 +/- -5 Shore A
Tear Resistance	D-624	50-125 PLI

*Varies based on color

Note: Physical properties can vary by product type. Information above applies to this product only.

Maintenance & Floor Care

Maintenance and floor care depend on the desired appearance of the installed product and the type of equipment used to maintain the flooring. Use only Ultimate RB recommended cleaners, disinfectant, and neutral PH, non-petroleum products. Do not use harsh chemicals. For specific products recommended by Ultimate RB, visit ULTIMATERB.com.

Warranty

ULTIMATE-TOUGH Rolls and Tiles carry a 5-year limited warranty for defects in material and workmanship. Refer to ULTIMATERB.com for limited warranty document.