



## ULTIMATE-DESIGN<sup>TM</sup> Rolls & Tiles



**ULTIMATE-DESIGN**  
recycled rubber flooring  
is an ideal choice for  
the varying demands of  
the commercial market.

### Features and Benefits

- Environmentally Friendly
- Durable
- Shock & Sound Absorbing
- Anti-Fatigue
- Easy to Clean
- Made in USA
- FloorScore Certified
- Custom Sizing & Colors
- Easy Installation
- Comes in Roll & Tile Options

### Applications:

- Retail Spaces, Offices & Restaurants
- Hospitals, Schools & Libraries
- Hospitality Areas
- Poolside Walkways
- Aerobic Fitness & Yoga Studios
- Sports Facilities and Arenas
- Golf & Ski Resorts
- Health & Fitness Centers

Admired by architects and designers. Recommended and selected by specifiers. Preferred by green building managers. ULTIMATE-DESIGN recycled rubber flooring has proven to be the floor of choice by those who desire sustainable, environmentally friendly, resilient flooring. ULTIMATE-DESIGN is available in a large number of colors and design options. Manufactured from vivid EPDM color granules, ULTIMATE-DESIGN rubber flooring can be blended to match your custom color palette, achieving virtually any color range for an unlimited number of applications. Schools, hospitals, retail spaces and corporate office buildings are common installations. Ultimate Design is FloorScore certified and meets the CHPS criteria for strict indoor air quality standards. In addition, ULTIMATE-DESIGN can contribute to multiple LEED credits under the U.S. Green Building Council's rating system.



### ULTIMATERB.com

904 NE 10<sup>th</sup> Avenue  
McMinnville, OR 97128  
(800) 525-5530 ▪ (503) 472-4691

Main manufacturing/shipping locations include Oregon and Ohio.

**Declare.**





# ULTIMATE-DESIGN™

## Rolls & Tiles



### Rolls

| Property   | Results                  |
|------------|--------------------------|
| Width*     | Standard<br>4' (1.22m)   |
| Thickness* | Standard:<br>4mm (.157") |
| Length*    | Standard:<br>25' (7.62m) |

### Maintenance & Floor Care

Maintenance and floor care depend on the desired appearance of the installed product and the type of equipment used to maintain the flooring. Use only Ultimate RB recommended cleaners, disinfectant, and neutral PH, non-petroleum products. Do not use harsh chemicals. For specific products recommended by Ultimate RB, visit [www.UltimateRB.com](http://www.UltimateRB.com).

### Warranty

Ultimate RB Rolled Rubber products carry a 5-year limited warranty for defects in material and workmanship. Refer to [UltimateRB.com](http://UltimateRB.com) for limited warranty document.

### Color Options

Please visit [www.UltimateRB.com](http://www.UltimateRB.com) for current available color options.



### Tiles

| Property   | Results                   |
|------------|---------------------------|
| Square     | 24" x 24" (0.61m x 0.61m) |
| Thickness* | Standard:<br>4mm (.157")  |

\* Custom available



### Rolled Goods Specifications

| Test Type               | ASTM   | Result                        |
|-------------------------|--------|-------------------------------|
| Shore Hardness          | D-2240 | 60 +/- 5                      |
| Density                 | D-395  | 63-94 lbs/ft <sup>3</sup>     |
| Elongation (at break)   | D-412  | 50-150%                       |
| Tensile Strength        | D-412  | 200-400 PSI                   |
| Compression Set         | D-395  | -15 to -45% @ 25%             |
| VOC Emissions           | D-5116 | 0.5 mg/m <sup>2</sup> or less |
| Resistance to Chemicals | F-925  | No Change                     |
| Static Load Limit       | F-970  | 400 lb/in                     |
| Critical Radiant Flux*  | E-648  | Class II                      |
| Coefficient of Friction | D-1894 | 0.75-1.50                     |
| Durometer               | D-2240 | 60 +/- 5 Shore A              |
| Tear Resistance         | D-264  | 50-125 PLI                    |

\* Custom available

Note: Physical properties can vary by product color.