



ULTIMATE-TOUGH™ TRU-LOCK™



The new TRU-LOCK tile is designed to cover 4 sq ft per tile. This makes estimating the quantity of tiles needed simple. TRU-LOCK provides all of the below benefits and more.

Features and Benefits

- Recycled Rubber
- Slip Resistant
- Limitless Color Options
- Environmentally Friendly
- Design Flexibility
- Easy Installation
- Sound & Shock Absorbing
- Easy Maintenance
- FloorScore Certified



ULTIMATE RB.com

904 NE 10th Avenue
McMinnville, OR 97128
(800) 525-5530 ▪ (503) 472-4691

Main manufacturing/shipping locations include Oregon and Ohio.

Applications:

- Home Gym Flooring
- Stationary Bike Matting
- Physical Therapy Facilities
- Ski & Snowboard Shops
- Ramps & Inclines
- Schools
- Weight Rooms & Gyms
- Baseball Areas
- Locker Rooms
- Heavy Traffic Areas
- Ice Rink Walkways
- Multi-Purpose Rooms

Flooring in athletic facilities must stand up to a variety of special demands ranging from the punishment of free weights to the shearing effect of ice skates. It must also provide noise reduction and a comfortable surface for the athletes. Recycled rubber flooring meets all these requirements. Ultimate-Tough TRU-LOCK tiles offer superior durability, resilience, sound absorption, spike resistance, and traction.

These tiles are engineered so precisely that the intricate interlocking pattern nearly disappears as the tiles are installed. The tab design holds the tiles together securely without the need for expensive adhesives, tapes, or the labor to apply them. The TRU-LOCK tiles can also be disassembled and re-assembled time and again without damaging the tiles. Also they offer great anti-fatigue qualities. Fabricated from fine rubber granules, their resilient properties give superior underfoot comfort to cushion the strain from running, exercising, and walking. On top of that, they are also very easy to clean.





ULTIMATE-TOUGH™ TRU-LOCK™



Typical Properties

Property	Results
Tile Sizes	Interlocking 24" x 24" inside to outside locking tabs
*Thicknesses	Standard: 8mm
Coverage	4 sq ft/tile
Tolerance	+/- 0.020"

*Custom available

ULTIMATE-TOUGH Zip-Tiles contain up to 92% recycled rubber material, manufactured in the USA, and are all covered by our Limited Warranties.

Color Options



NO. 106
Black




NO. 226
Grey



NO. 236
Blue/Grey




NO. 250
Green



NO. 231
Blue



NO. 10518
Cocoa/Eggshell



NO. 292
Bright Red

Brick Red, Purple, Teal, Green/Grey and other custom colors available by request.



Specifications

Test Type	ASTM	Result
Shore Hardness	D-2240	65 +/- 5
Density	D-395	63-94 lbs/ft ³
Elongation (at break)	D-412	50-150%
Tensile Strength	D-412	200-400 PSI
Compression Set	D-395	-15 to -45% @ 25%
VOC Emissions	D-5116	0.5 mg/m ² or less
Resistance To Chemicals	F-925	No Change
Static Load Limit	F-970	Passes, 150 PSI
Surface Flammability	D-2895	Pass
Die-C Tear	D-624	80 min
Coefficient of Friction	D-1894	0.75-1.50
Durometer	D-2240	60 +/- 5 Shore A
Tear Resistance	D-624	50-125 PLI

*Varies based on color

Note: Physical properties can vary by product type. Information above applies to this product only.

Maintenance & Floor Care

Maintenance and floor care depend on the desired appearance of the installed product and the type of equipment used to maintain the flooring. Use only Ultimate RB recommended cleaners, disinfectant, and neutral PH, non-petroleum products. Do not use harsh chemicals. For specific products recommended by Ultimate RB, visit ULTIMATERB.com.

Warranty

Ultimate-Tough TRU-LOCK tiles carry a 5-year limited warranty for defects in material and workmanship. Refer to ULTIMATERB.com for limited warranty document.